



*UNDERGROUND & OVERHEAD CONSTRUCTION • HORIZONTAL DIRECTIONAL DRILLING • LINE MAINTENANCE*

# ***TOOLS & EQUIPMENT***

## **CATALOG**

# **PULL ROPE & PULL TAPE**





# THE RIGHT PRODUCTS, THE RIGHT SERVICE

## The Biggest Range of Wire Pulling Accessories and Drilling Fluid Additives

Are you planning a building project and looking for the most amazing prices on tools and accessories? Build It Right, Inc. is your one stop shop that provides the biggest range of products for drilling, cabling, and wire pulling in the U.S. Offering the highest quality products backed by our years of knowledge and expertise in the industry, you can easily build with confidence and convenience with everything you need at your fingertips.

## Offering the Right Accessories at the Right Price for Any Building Project

Build It Right, Inc. was founded on the needs of our customers to find the most useful and appropriate building products and accessories at the most amazing prices. Our focus is on the customer experience, which is why we deliver exceptional customer service through the most knowledgeable advice and high quality products. Whether you need wire pulling tools, Cetco drilling fluids, drilling polymer products and more, our team is here to help you find exactly what you need at the lowest price.

## Are You Looking for Directional Drilling Tools or Horizontal Directional Drilling Parts?

At Build It Right, we stock the most popular brands that deliver quality no matter what you need to build. Have your Cetco and Bentonite drilling fluids shipped right to your door so that you can build with confidence. You can also order your Cetco and Bentonite drilling fluids by the pallet! Install ducts with efficiency with duct installation range of products, or work quickly when installing cables with our easy to use cable roller range that delivers affordability and speed no matter how large your project is.

## Shop for Cable Puller Products and Accessories Today!

Rather than blowing your building project budget, shop for the most affordable high quality products and accessories with Build It Right, Inc. Offering nationwide shipping and the most competitive prices in the industry, our goal is to ensure that your project is a success. The right products. The right service. Shop Online today or call our team at 1-888-206-3044 to find out more.





## DOUBLE BRAIDED PULLING ROPE



High tensile low stretch polyester double braided pulling rope with factory spliced pulling eyes at each end.

- High Strength Premium Grade Double Braid Polyester Rope for use on high strength cable pullers
- Low Elongation
- Torque-free
- Factory Spliced Pulling Eyes
- Custom Continuous Lengths Available

Part Number	Diameter (in)	Length (ft)	Minimum Break Strength	Approximate Density (lb/100 ft.)	Approximate Package Weight
CDB120600	3/8"	600'	5,000 lb	4.5 lb	27.0 lb
CDB121200	3/8"	1,200'	5,000 lb	4.5 lb	54.0 lb
CDB140600	7/16"	600'	7,500 lb	6.1 lb	37.0 lb
CDB141200	7/16"	1,200'	7,500 lb	6.1 lb	74.0 lb
CDB160300	1/2"	300'	9,500 lb	8.1 lb	25.0 lb
CDB160600	1/2"	600'	9,500 lb	8.1 lb	49.0 lb
CDB161200	1/2"	1,200'	9,500 lb	8.1 lb	98.0 lb
CDB180300	9/16"	300'	16,150 lb	10.0 lb	30.0 lb
CDB180600	9/16"	600'	16,150 lb	10.0 lb	60.0 lb
CDB181200	9/16"	1,200'	16,150 lb	10.0 lb	120.0 lb
CDB200300	5/8"	300'	18,000 lb	13.0 lb	39.0 lb
CDB200600	5/8"	600'	18,000 lb	13.0 lb	78.0 lb
CDB201200	5/8"	1,200'	18,000 lb	13.0 lb	156.0 lb
CDB240300	3/4"	300'	26,000 lb	18.0 lb	54.0 lb
CDB240600	3/4"	600'	26,000 lb	18.0 lb	108.0 lb
CDB241200	3/4"	1,200'	26,000 lb	18.0 lb	216.0 lb
CDB280300	7/8"	300'	32,000 lb	25.0 lb	75.0 lb
CDB280600	7/8"	600'	32,000 lb	25.0 lb	150.0 lb
CDB281200	7/8"	1,200'	32,000 lb	25.0 lb	300.0 lb
CDB320300	1"	300'	42,000 lb	32.0 lb	96.0 lb
CDB320600	1"	600'	42,000 lb	32.0 lb	192.0 lb
CDB321200	1"	1,200'	42,000 lb	32.0 lb	384.0 lb
CDB330600	1-1/8"	600'	47,900 lb	46.0 lb	276.0 lb
CDB331200	1-1/8"	1,200'	47,900 lb	46.0 lb	552.0 lb
CDB340600	1-1/4"	600'	56,200 lb	54.0 lb	324.0 lb
CDB341200	1-1/4"	1,200'	56,200 lb	54.0 lb	648.0 lb
CDB360600	1-1/2"	600'	73,380 lb	75.0 lb	450.0 lb
CDB361200	1-1/2"	1,200'	73,380 lb	75.0 lb	900.00 lb



## 3 STRAND TWISTED YELLOW POLYPROPYLENE ROPE



Premium grade U.V. Stabilized polypropylene fiber

- Strong Lightweight Economical Rope
- Good Strength – Moderate Stretch
- Medium Laid – Balanced Construction
- Resistant to Rot, Mildew & Petroleum Products
- Continuous Length Long Length Reels Available
- Stores Wet without Fiber Damage
- UV Stabilized Fiber Floats
- Versatile

Part Number	Diameter (in)	Length (ft)	Minimum Break Strength	Approximate Density (lb./100 ft.)	Approximate Package Weight
TWPY060600	3/16"	600'	720 lb	0.7	4.2 lb
TWPY061200	3/16"	1,200'	720 lb	0.7	8.4 lb
TWPY066000	3/16"	6,000'	720 lb	0.7	42.0 lb
TWPY080100	1/4"	100'	1,250 lb	1.2	1.2 lb
TWPY080300	1/4"	300'	1,250 lb	1.2	3.6 lb
TWPY080600	1/4"	600'	1,250 lb	1.2	7.2 lb
TWPY081200	1/4"	1,200'	1,250 lb	1.2	14.4 lb
TWPY082400	1/4"	2,400'	1,250 lb	1.2	28.8 lb
TWPY085000	1/4"	5,000'	1,250 lb	1.2	60.0 lb
TWPY100600	5/16"	600'	1,710 lb	1.8	10.8 lb
TWPY101200	5/16"	1,200'	1,710 lb	1.8	21.6 lb
TWPY120100	3/8"	100'	2,440 lb	2.8	2.8 lb
TWPY120300	3/8"	300'	2,440 lb	2.8	8.4 lb
TWPY120600	3/8"	600'	2,440 lb	2.8	16.8 lb
TWPY121200	3/8"	1,200'	2,440 lb	2.8	33.6 lb
TWPY122400	3/8"	2,400'	2,440 lb	2.8	67.2 lb
TWPY123600	3/8"	3,600'	2,440 lb	2.8	100.8 lb
TWPY160100	1/2"	100'	3,780 lb	4.7	4.7 lb
TWPY160300	1/2"	300'	3,780 lb	4.7	14.1 lb
TWPY160600	1/2"	600'	3,780 lb	4.7	28.2 lb
TWPY161200	1/2"	1,200'	3,780 lb	4.7	56.4 lb
TWPY162400	1/2"	2,400'	3,780 lb	4.7	112.8 lb
TWPY200100	5/8"	100'	5,600 lb	7.5	7.5 lb
TWPY200600	5/8"	600'	5,600 lb	7.5	45.0 lb
TWPY201200	5/8"	1,200'	5,600 lb	7.5	90.0 lb
TWPY202400	5/8"	2,400'	5,600 lb	7.5	180.0 lb
TWPY240100	3/4"	100'	7,650 lb	10.7	10.7 lb
TWPY240300	3/4"	300'	7,650 lb	10.7	32.1 lb
TWPY240600	3/4"	600'	7,650 lb	10.7	64.2 lb
TWPY241200	3/4"	1,200'	7,650 lb	10.7	128.4 lb
TWPY320100	1"	100'	12,600 lb	18.0	18.0 lb
TWPY320600	1"	600'	12,600 lb	18.0	108.0 lb
TWPY321200	1"	1,200'	12,600 lb	18.0	216.0 lb
TWPY340600	1-1/4"	600'	18,900 lb	27.0	162.0 lb
TWPY360600	1-1/2"	600'	26,800 lb	38.0	230.0 lb
TWPY400600	2"	600'	46,800 lb	69.0	414.0 lb

## SPIRAL WRAPPED LIGHT DUTY POLY TWINE



Ideal for many types of pulls including pulling rope through conduit. Will not rot, mildew or rust. Can be left in conduit for future use. Ships in plastic pail for ease of use and storage.

Part Number	Size	Length (ft)	Minimum Tensile Strength (lb)	Package Type
SRPT6500B	650	6,500'	210 lb	Pail
SRPT2200B	220	2,200'	500 lb	Pail



## DETECTABLE WOVEN POLYESTER PULLING TAP 22 GAUGE CONDUCTOR



- Provides a reliable means of locating cable in conduit. Sequentially footage marked
- High Strength – Low Stretch Detectable Pulling Tape
- 22 Gauge Detectable Copper Conductor
- Proprietary Pre-Lubrication to Reduce Coefficient of Friction
- Continuous Length Reels
- Packaged on Heavy Duty Black Plastic Reels
- Custom Continuous Length Reels Available

Part Number	Tensile Strength	Approximate Width (in)	Length (ft)	Maximum Reel Length (ft)
WPD12503000	1,250 lb	1/2"	3,000'	100,000'
WPD12505000	1,250 lb	1/2"	5,000'	100,000'
WPD18003000	1,800 lb	5/8"	3,000'	60,000'
WPD18005000	1,800 lb	5/8"	5,000'	60,000'
WPD25003000	2,500 lb	3/4"	3,000'	45,000'
WPD25005000	2,500 lb	3/4"	5,000'	45,000'



## WOVEN POLYESTER CABLE-PULLING TAPE



- High Strength – Low Stretch Polyester Pulling Tape
- Accurate Sequential Footage Markings
- Low Elongation
- Proprietary Pre-Lubrication to Reduce Coefficient of Friction
- Continuous Length Reels from 500 ft. – 100,000 ft.
- Packaged on Heavy Duty Black Plastic Reels
- Custom Continuous Length Reels Available
- High tensile strength, low stretch
- Printed sequential footage markings for accurate measurements
- Easily blown through conduits or ducts
- Available with or without detectable tracer wire

Part Number	Tensile Strength	Approximate Width (in)	Length (ft)	Maximum Reel Length (ft)
WP12500500	1,250 lb	1/2"	500'	100,000'
WP12501000	1,250 lb	1/2"	1,000'	100,000'
WP12501500	1,250 lb	1/2"	1,500'	100,000'
WP12503000	1,250 lb	1/2"	3,000'	100,000'
WP12505000	1,250 lb	1/2"	5,000'	100,000'
WP18000500	1,800 lb	5/8"	500'	60,000'
WP18001000	1,800 lb	5/8"	1,000'	60,000'
WP18001500	1,800 lb	5/8"	1,500'	60,000'
WP18003000	1,800 lb	5/8"	3,000'	60,000'
WP18050000	1,800 lb	5/8"	5,000'	60,000'
WP25000500	2,500 lb	3/4"	500'	45,000'
WP25001000	2,500 lb	3/4"	1,000'	45,000'
WP25001500	2,500 lb	3/4"	1,500'	45,000'
WP25003000	2,500 lb	3/4"	3,000'	45,000'
WP25005000	2,500 lb	3/4"	5,000'	45,000'



## 3-IN-1 PULL TAPE



- 3-in-1: thread, measure, and pull
- Sequential footage markings
- Easy center pull bucket
- Reduce tension at start of pull
- Low stretch

Part Number	Tensile Strength	Typical Bowline Strength	Typical Knot Strength	Pail Quantity	Pails Per Pallet
WPB4004500	400 lb	190 lb	300 lb	4,500'	48
WPB12502100	1,250 lb	595 lb	940 lb	2,100'	48
WPB18001300	1,800 lb	830 lb	1,400 lb	1,300'	48
WPB2500750	2,500 lb	1,190 lb	1,875 lb	750'	48



## CONDUIT MEASURING TAPE



- Accurate Sequential Footage Markings
- Accurately Fish & Measure Conduit Runs in One Operation
- 130 lb. Tensile Strength
- Low Elongation
- Rot & Mildew Resistant
- Continuous Length 3000 ft. Metal Reels

Part Number	Size (in)	Width (in)	Minimum Tensile Strength	Length (ft)
WPC130	3/16"	1/4"	130 lb	3,000'



## POWERPLEX 12 STRAND POLYESTER



- High strength and low elongation
- Easy to splice and handle
- Coated with Rhinokote coating for added abrasion resistance
- Balanced, torque-free construction

Size	Diameter	Circ.	Tensile Strength
3W-3/8"	3/8"	1.24"	5,400 lb
3W-1/2"	1/2"	1.48"	11,250 lb
3W-5/8"	5/8"	1.98"	16,650 lb



## PAD MOUNT TRANSFORMER SLINGS 48"



This rope is designed to lift a single phase transformer. Each leg is 48' long and coated for increased abrasion resistance. In addition, this sling has an adjustable third leg for use in securing the transformer door in an upward position when open.

- Adjustable
- Adjustable third leg
- Coated for increased durability and abrasion resistance
- Each leg is 48" Long







## **Stocking Locations**

**1300 National Ave Unit B  
Addison, IL 60101**

**1440 Kings HWY  
Haddon Heights, NJ 08035**

**888-206-3044  
sales@builditright.us  
www.builditright.us**