



UNDERGROUND & OVERHEAD CONSTRUCTION • HORIZONTAL DIRECTIONAL DRILLING • LINE MAINTENANCE

TOOLS & EQUIPMENT

CATALOG

SAFETY EQUIPMENT & PPE



THE RIGHT PRODUCTS, THE RIGHT SERVICE

The Biggest Range of Wire Pulling Accessories and Drilling Fluid Additives

Are you planning a building project and looking for the most amazing prices on tools and accessories? Build It Right, Inc. is your one stop shop that provides the biggest range of products for drilling, cabling, and wire pulling in the U.S. Offering the highest quality products backed by our years of knowledge and expertise in the industry, you can easily build with confidence and convenience with everything you need at your fingertips.

Offering the Right Accessories at the Right Price for Any Building Project

Build It Right, Inc. was founded on the needs of our customers to find the most useful and appropriate building products and accessories at the most amazing prices. Our focus is on the customer experience, which is why we deliver exceptional customer service through the most knowledgeable advice and high quality products. Whether you need wire pulling tools, Cetco drilling fluids, drilling polymer products and more, our team is here to help you find exactly what you need at the lowest price.

Are You Looking for Directional Drilling Tools or Horizontal Directional Drilling Parts?

At Build It Right, we stock the most popular brands that deliver quality no matter what you need to build. Have your Cetco and Bentonite drilling fluids shipped right to your door so that you can build with confidence. You can also order your Cetco and Bentonite drilling fluids by the pallet! Install ducts with efficiency with duct installation range of products, or work quickly when installing cables with our easy to use cable roller range that delivers affordability and speed no matter how large your project is.

Shop for Cable Puller Products and Accessories Today!

Rather than blowing your building project budget, shop for the most affordable high quality products and accessories with Build It Right, Inc. Offering nationwide shipping and the most competitive prices in the industry, our goal is to ensure that your project is a success. The right products. The right service. Shop Online today or call our team at 1-888-206-3044 to find out more.



Safety Equipment & PPE

Head Protection

pg. 4

Eye Protection

pg. 6

Body Harnesses

pg. 10

Lanyards

pg. 14

Lifelines

pg. 16

Hand Protection

pg. 18

High Visibility Apparel

pg. 26

AC Blowers

pg. 32

Manhole Products

pg. 33

Signs & Safety Cones

pg. 34

Arrow Boards

pg. 36



GRANITE™ CAP STYLE HARD HAT

Radians Granite™ cap style hard hat has a high-density polyethylene construction, it is designed to meet ANSI Z89.1, Type 1 and Class G and E protection. These cap style hard hats offer a very adjustable and comfortable fit with either a ratcheting or pinlock suspension and a pillow brow padding. Made in the USA and imprinting available in house makes customizing these hard hats not only a painless process but will allow your company to exude professionalism and to be easily recognizable and with a quick turnaround. Vented, Class C cap style also available.

- Pillowed Brow Pad
- Nylon Crown Strap Suspension
- Vertical Height Adjustment
- High Density Polyethylene Construction
- Universal Accessory Slots
- Available in Standard or Vented Version

Add your logo!



Part No.	Ratchet Suspension	White	Yellow	Red	Orange	Gray	Dark Gray	Green	Blue	Ocean Blue	Hi-Vis Green	Hi-Vis Orange
GHR4-Color	4 Point	X	X	X	X	X		X	X	X	X	X
GHR6-Color	6 Point	X	X	X	X	X		X	X		X	X
GHR4V-Color	Vented 4 Point	X	X	X			X	X	X		X	X
GHP4-Color	4 Point	X	X	X			X					
GHP6-Color	6 Point	X										



REPLACEMENT SUSPENSIONS



Part No.	Suspension
HHSP4	4 Point Pin-lock
HHSR4	4 Point Ratchet
HHSP6	6 Point Pin-lock
HHSR6w	6 Point Pin-lock



QUARTZ™ FULL BRIM HARD HAT

Radians Quartz™ full brim hard hat has a high-density polyethylene construction, it is designed to meet ANSI Z89.1, Type 1 and Class G and E protection. These full brim hard hats will provide their wearer with added protection from dropped objects as well as sunburns. They offer a very adjustable and comfortable fit with either a ratcheting or pinlock suspension and a pillow brow padding. Made in the USA and imprinting available in house makes customizing these hard hats not only a painless process but will allow your company to exude professionalism and to be easily recognizable and with a quick turnaround. Vented, Class C full brim style also available.

- Pillowed Brow Pad
- Nylon Crown Strap Suspension
- Vertical Height Adjustment
- High Density Polyethylene Construction
- Full Profile, Full Brim
- Available in Standard or Vented Version

Add your logo!



Part No.	Ratchet Suspension	White	Yellow	Red	Orange	Gray	Dark Gray	Green	Blue	Hi-Vis Green	Hi-Vis Orange
QHR4-Color	4 Point	X	X	X	X	X		X	X	X	X
QHR6-Color	6 Point	X	X	X	X	X	X	X	X	X	X
QHR4V-Color	Vented 4 Point	X	X	X							
QHP4-Color	4 Point	X									
QHP6-Color	6 Point	X									



EASILY CLIPS INTO EXISTING TABS

HARD HAT CHIN STRAP

- Two Point Attachment
- Black Elastic



HHCS2





ZENON®

Eyeglasses are not safety glasses unless both the lenses and frame are in compliance with the specifications for safety eye-wear described in the ANSI Z87.1 Standard. Radians offers a full line of safety eye-wear, including foam-lined, anti-fog, over-the-glass, bifocal, and polarized eye-wear. With varying temple, nose-piece, and lens features, we have the perfect eye-wear solution for you.



ZENON Z12™

Rimless Safety Glasses with Black Temple, Clear Lens and Anti-Scratch Coating

250-01-0000

- CE EN 166 Certified
- SIZE: OS
- PACKED: 144 Pair/Case
- STOCK TYPE: Stock



ZENON Z12™

Rimless Safety Glasses with Black Temple, Gray Lens and Anti Scratch Coating

250-01-0001

- SIZE: OS
- PACKED: 144 Pair/Case
- STOCK TYPE: Stock



ZENON Z12™

Rimless Safety Glasses with Black Temple, Gray Lens and Anti Scratch Coating

250-01-0001

- SIZE: OS
- PACKED: 144 Pair/Case
- STOCK TYPE: Stock



ZENON Z12™

Rimless Safety Glasses with Clear Temple, Clear Lens and Anti-Scratch Coating

250-01-0900

- SIZE: OS
- PACKED: 144 Pair/Case
- STOCK TYPE: Stock



ZENON Z12™

Rimless Safety Glasses with Clear Temple, Clear Lens and Anti Scratch/Anti-Fog Coating

250-01-0920

- SIZE: OS
- PACKED: 144 Pair/Case
- STOCK TYPE: Stock



ZENON Z12™

Rimless Safety Glasses with Clear Temple, Clear Lens

250-01-0980

- SIZE: OS
- PACKED: 144 Pair/Case
- STOCK TYPE: Stock



ZENON Z12™ FOAM

Rimless Safety Glasses with Black Temple, Clear Lens, Foam Padding and Anti-Scratch/Anti-Fog Coating

250-01-F020

- Meets Z87.1+
- SIZE: OS
- PACKED: 144 Pair/Case
- STOCK TYPE: Stock



ZENON Z13™

Rimless Safety Glasses with Clear Temple, Clear Lens and Anti Scratch Coating

250-06-0000

- SIZE: OS
- PACKED: 144 Pair/Case
- STOCK TYPE: Stock



ZENON Z13™

Rimless Safety Glasses with Clear Temple, Clear Lens and Anti Scratch/Anti-Fog Coating

250-06-0020

- SIZE: OS
- PACKED: 144 Pair/Case
- STOCK TYPE: Stock



RECON®



RECON
Rimless Safety Glasses with Clear Temple,
Clear Lens and Anti-Scratch Coating
250-32-0020

- CSA
- SIZE: OS
- PACKED: 144 Pair/Case
- STOCK TYPE: Stock



RECON
Rimless Safety Glasses with Clear Temple,
Clear Lens and Anti-Scratch/Anti-Fog 3Sixty™ Coating
250-32-0520

- ANSI Z87.1-2015
- SIZE: OS
- PACKED: 144 Pair/Case
- STOCK TYPE: Stock



RECON
Rimless Safety Glasses with Gloss Black Temple,
Gray Lens and Anti-Scratch/Fog-less 3Sixty™ Coating
250-32-0521

- ANSI Z87.1-2015
- SIZE: OS
- PACKED: 144 Pair/Case
- STOCK TYPE: Stock

ANSER®



ANSER™
Semi-Rimless Safety Glasses with Black Frame,
Clear Lens and Anti-Scratch/Anti-Fog Coating
250-AN-10111

- SIZE: OS
- PACKED: 144 Pair/Case
- STOCK TYPE: Stock



ANSER™
Semi-Rimless Safety Glasses with Black Frame,
Gray Lens and Anti-Scratch Coating
250-AN-10112

- SIZE: OS
- PACKED: 144 Pair/Case
- STOCK TYPE: Stock



ANSER™
Semi-Rimless Safety Glasses with Black Frame,
I/O Lens and Anti-Scratch Coating
250-AN-10114

- SIZE: OS
- PACKED: 144 Pair/Case
- STOCK TYPE: Stock



ANSER™
Semi-Rimless Safety Glasses with Black Frame,
Gray Lens and Anti-Scratch/Anti-Fog Coating
250-AN-10526

- SIZE: OS
- PACKED: 144 Pair/Case
- STOCK TYPE: Stock



ANSER™
Semi-Rimless Safety Glasses with Black Frame,
Clear Lens and FogLess® 3Sixty™ Coating
250-AN-10520

- Includes Neck Cord
- SIZE: OS
- PACKED: 144 Pair/Case
- STOCK TYPE: Stock



ANSER™
Semi-Rimless Safety Glasses with Black Frame,
Gray Lens and FogLess® 3Sixty™ Coating
250-AN-10521

- Includes Neck Cord
- SIZE: OS
- PACKED: 144 Pair/Case
- STOCK TYPE: Stock



FOG BUSTER

Part NO.	Materials	Packaging
252-FB30	Pre Moistened Towelettes	30 applications, 6 boxes per case



LENS CLEANING STATION

Part No.	Materials	Packaging
252-LCS08	Spry Cleaner Lint-Free Cleaner	8 oz bottle two 300 ct tissue boxes



LENS CLEANING TOWELETTES

Part NO.	Materials	Packaging
252-FB30	Pre Moistened Towelettes	100 towelettes, 10 dispensers per case

UNIVERSAL FLEX SIDE SHIELDS

- Weaves through the temple for added side protection
- Molded to a bendable softness
- Temple will still fold correctly
- No parts or tools required
- Meets ANSI Z87.1+ requirements

Part NO.	Color
252-FX-0001	Clear



BLACK NECK CORDS

- Keeps glasses close at hand for a safer workplace

Part NO.	
252-L401	Rugged Nylon
252-L404	Economy Slim Nylon
252-L407	Adjustable Sports Cord





HONEYWELL BW™ CLIP4

When you've got your hands full in the field, you need no hassle gas detection you can count on: The Honeywell BW™ Clip4 four-gas detector

Wearable, easy multi-gas detection that's always on. No charging, no battery replacement, no hassle. Simpler, low cost of ownership guaranteed by the Honeywell commitment to quality, and backed by a full ecosystem of supporting technologies. When you clip on the Honeywell BW™ Clip4 you know – it's on. Always On: 2-Year Continuous Runtime. Once activated, you can rest assured that the Honeywell BW™ Clip4 is always on. The Honeywell BW™ Clip4 is easy to wear and use. Lower your maintenance costs with two years of continuous runtime without charging and no battery or sensor replacements. Simply turn your new detector on and then after two years replace it for a new one.

- 2 year continuous runtime
- It's always on
- Simple one-button operation
- Low cost of ownership
- H2S, CO, LEL, O2
- IntelliDoX compatible



Category	Humidity Range	Sensor Range	Alarm	Battery	Data-logging	User Options
Multi-Gas	5% - 95%	H2S (0 - 100ppm), CO (0 - 100ppm), O2 (0-25% vol), LEL (0-100% LEL)	Audible, Visual Vibrating	Run Time: 2 Hours	70 most recent events	Adjusts STEL period (5 - 15 minutes in 1 minute intervals)

Part No	Description
BWC4-AG	Replacement alligator clip for BW Clip4t
BWC4-B-C	BWC4 - O2, LEL, H2S, CO, Black, CN/NZ
BWC4-B-E	BW Clip4 (O2, LEL, H2S, CO), EMEA version, black housing
BWC4-B-N	4-gas detector (O2, LEL, H2S, CO) - black housing, North American version
BWC4-B-R	BW Clip4 (O2, LEL, H2S, CO), Customs Union certified, black housing
BWC4-BC	Replacement back case for BW Clip4
BWC4-FCLCD-B	Replacement front case including LCD for BW Clip4 (black)
BWC4-FCLCD-Y	Replacement front case including LCD for BW Clip4 (yellow)
BWC4-SCREW	Replacement screw kit for BW Clip4 (kit of 30)
BWC4-SS	Replacement sensor screens for BW Clip4 (kit of 2)



ARC FLASH CONSTRUCTION HARNESSSES

The Arc Flash Aramid Harnesses, built for utility and electrical workers, deliver dependable protection plus all-day comfort. Designed with our premium aramid ASTM/NFPA approved webbing and Nomex® shoulder, waist and leg pads, our Arc Flash harnesses feature either coated, corrosion-resistant dielectric hardware or standard hardware protected with our unique component backer. This durable harness provides superior protection in an arc event situation. Offered in a variety of configurations.



020-1252

ARC FLASH CONSTRUCTION HARNESS

DE 3D, DE QC Chest, DE FD, DE QC Legs

- Dielectric dorsal D-ring
- Dielectric front D-ring
- Dielectric side positioning D-rings
- Dielectric mating buckle torso adjusters
- Dielectric quick-connect chest
- Dielectric quick-connect legs
- 40Cal/700F rated aramid webbing
- Shoulder, waist and leg pads
- User capacity 130-310 lb. ANSI, 420 lb. OSHA
- Meets ANSI Z359.11, ASTM F887, NFPA 70E

See Size Chart on Next Page.



Arc Flash vs. Dielectric

Arc Flash ARC FLASH harnesses are only required to meet the ASTM F997 standard. This standard does not address the arc control capability of any buckles or hardware. Product may meet the Arc Flash standard, but do not include the dielectric hardware. These still qualify under the ASTM standard.



Dielectric Front D-Ring



Aramid Webbing



Dielectric Dorsal D-Ring



Dielectric Side Positioning D-Ring



Dielectric Quick Connect Chest



Dielectric Mating Buckle Torso Adjusters



020-1268

ARC FLASH FULL BODY HARNESS

DE 3D, DE QC Chest, DE FD, TB Legs

- Dielectric dorsal D-ring
- Dielectric side positioning D-rings
- Dielectric mating buckle torso adjusters
- Dielectric quick-connect chest
- Tongue buckle legs
- 40Cal/700F rated aramid webbing
- Shoulder, waist and leg pads
- User capacity 130-310 lb. ANSI, 420 lb. OSHA
- Meets ANSI Z359.11, ASTM F887, NFPA 70E



020-1346

ARC FLASH CONSTRUCTION HARNESS

3D, MB Chest, TB Legs

- Dorsal D-ring
- Side positioning D-rings
- Mating buckle torso adjusters
- Mating buckle chest
- Tongue buckle legs
- 40Cal/700F rated aramid webbing
- Shoulder, waist and leg pads
- User capacity 130-310 lb. ANSI, 420 lb. OSHA
- Meets ANSI Z359.11, ASTM F887, NFPA 70E



020-1260

ARC FLASH CONSTRUCTION HARNESS

DE 3D, DE QC Chest, TB Legs

- Dielectric D-ring
- Dielectric positioning D-rings
- Dielectric Buckle torso adjusters
- Tongue buckle legs
- 40Cal/700F rated aramid webbing
- Shoulder, waist and leg pads
- User capacity 130-310 lb. ANSI, 420 lb. OSHA
- Meets ANSI Z359.11, ASTM F887, NFPA 70E



5

ARC FLASH FULL BODY HARNESS

DE 3D, DE MB Chest/Leg

- Dielectric dorsal D-ring
- Dielectric side positioning D-rings
- Dielectric mating buckle torso adjusters
- Dielectric mating buckle legs
- 40Cal/700F rated aramid webbing
- Shoulder, waist and leg pads
- User capacity 130-310 lb. ANSI, 420 lb. OSHA
- Meets ANSI Z359.11, ASTM F887, NFPA 70E

020-1276



6

ARC FLASH FULL BODY HARNESS

DE 1D, DE MB Chest, TB Legs

- Dielectric dorsal D-ring
- Dielectric mating buckle torso adjusters
- Dielectric mating buckle chest
- Tongue buckle legs
- 40Cal/700F rated aramid webbing
- Shoulder, waist and leg pads
- User capacity 130-310 lb. ANSI, 420 lb. OSHA
- Meets ANSI Z359.11, ASTM F887, NFPA 70E

020-1284



7

ARC FLASH FULL BODY HARNESS

DE 1D, DE MB Chest/Legs

- Dielectric dorsal D-ring
- Dielectric mating buckle torso adjusters
- Dielectric mating buckle chest
- Dielectric mating buckle legs
- 40Cal/700F rated aramid webbing
- Shoulder, waist and leg pads
- User capacity 130-310 lb. ANSI, 420 lb. OSHA
- Meets ANSI Z359.11, ASTM F887, NFPA 70E

020-1292



8

ARC FLASH FULL BODY HARNESS

DE 1D, MB Chest, TB Legs

- Dorsal D-ring
- Friction buckle torso adjusters
- Mating buckle chest
- Tongue buckle legs
- 40Cal/700F rated aramid webbing
- Shoulder, waist and leg pads
- User capacity 130-310 lb. ANSI, 420 lb. OSHA
- Meets ANSI Z359.11, ASTM F887, NFPA 70E

020-1354

Arc Flash Harness Sizes

Harness	X-SMALL	SMALL	MEDIUM	LARGE	X-LARGE	2X	3X
1	020-1250	020-1251	020-1252	020-1253	020-1254	020-1255	020-1256
2	020-1258	020-1259	020-1260	020-1261	020-1262	020-1263	020-1264
3	020-1344	020-1345	020-1346	020-1347	020-1348	020-1349	020-1350
4	020-1266	020-1267	020-1268	020-1269	020-1270	020-1271	020-1272
5	020-1274	020-1275	020-1276	020-1277	020-1278	020-1279	020-1280
6	020-1282	020-1281	020-1284	020-1285	020-1286	020-1287	020-1288
7	020-1290	020-1291	020-1292	020-1293	020-1294	020-1295	020-1296
8	020-1352	020-1353	020-1354	020-1354	020-1356	020-1357	020-1358



ARC FLASH CONSTRUCTION HARNESSSES

The Arc Flash Nylon Harness delivers comfort and easy movement in the confines of a bucket and other arc-rated applications. Equipped with heavy duty mill spec ASTM/NFPA approved webbing and coated, corrosion-resistant dielectric hardware. Offered in a variety of configurations, in a pullover or traditional H-style design.

1



SW77125-UTQC

ARC FLASH CONSTRUCTION HARNESS

DE 1D, Soft Sternal Loop, DE MB Torso, DE QC Legs

- Pullover construction
- Dielectric dorsal D-ring
- Soft loop front D-ring
- Dielectric quick-connect legs
- 40Cal/550 rated aramid webbing
- User capacity 130-310 lb. ANSI, 420 lb. OSHA
- Meets ANSI Z359.11, ASTM F887, NFPA 70E

See Size Chart on Next Page.



Arc Flash vs. Dielectric

Arc Flash ARC FLASH harnesses are only required to meet the ASTM F997 standard. This standard does not address the arc control capability of any buckles or hardware. Product may meet the Arc Flash standard, but do not include the dielectric hardware. These still qualify under the ASTM standard.



ASTM/NFPA
Approved Webbing



Load Indicator



Dorsal D-Ring



Torso Adjusters



Quick-Connect Legs



Soft Loop
Front D-Ring

2



SW77125-UTQC-3L

ARC FLASH CONSTRUCTION HARNESS

Soft Dorsal & Sternal Loop, DE MB Torso, DE QC Legs

- Pullover construction
- Soft loop dorsal D-ring
- Soft loop front D-ring
- Dielectric mating buckle torso adjusters
- Dielectric quick-connect legs
- 40Cal/550 rated aramid webbing
- User capacity 130-310 lb. ANSI, 420 lb. OSHA
- Meets ANSI Z359.11, ASTM F887, NFPA 70E

3



SW77225-UT3QC

ARC FLASH CONSTRUCTION HARNESS

DE 1D, DE MB Torso, DE QC Chest/Legs

- Dielectric dorsal D-ring
- Dielectric mating buckle torso adjusters
- Dielectric quick-connect chest
- Dielectric quick-connect legs
- 40Cal/550 rated aramid webbing
- User capacity 130-310 lb. ANSI, 420 lb. OSHA
- Meets ANSI Z359.11, ASTM F887, NFPA 70E



SW77125-UTQC
(Back)



SW77225-UTQC

ARC FLASH CONSTRUCTION HARNESS

DE 1D, DE MB Torso, DE MB Chest, DE QC Legs

- Dielectric dorsal D-ring
- Dielectric mating buckle torso adjusters
- Dielectric mating buckle chest
- Dielectric quick connect legs
- 40Cal/550 rated aramid webbing
- User capacity 130-310 lb. ANSI, 420 lb. OSHA
- Meets ANSI Z359.11, ASTM F887, NFPA 70E



SW77225-UT2QCSL

ARC FLASH CONSTRUCTION HARNESS

Soft Loop, 1D, DE MB Torso, D

- Soft loop dorsal D-ring
- Dielectric mating buckle
- Dielectric mating buckle chest
- Dielectric quick-connect legs
- 40Cal/550 rated aramid webbing
- User capacity 130-310 lb. ANSI, 420 lb. OSHA
- Meets ANSI Z359.11, ASTM F887, NFPA 70E

Arc Flash Harness Sizes						
Harness	X-SMALL	SMALL/MEDIUM	LARGE/X-LARGE	2X	3X	4X
1	SW77125-UTQC-XS	SW77125-UTQC-S/M	SW77125-UTQC-L/XL	SW77125-UTQC-2X	SW77125-UTQC-3X	SW77125-UTQC-4X
2	SW77125-UTQC-SL-XS	SW77125-UTQC-SL-S/M	SW77125-UTQC-SL-L/XL	SW77125-UTQC-SL-2X	SW77125-UTQC-SL-3X	SW77125-UTQC-SL-4X
3	SW77225-UT3QC-XS	SW77225-UT3QC-S/M	SW77225-UT3QC-L/XL	SW77225-UT3QC-2X	SW77225-UT3QC-3X	SW77225-UT3QC-4X
4	SW77225-UTQC-XS	SW77225-UTQC-S/M	SW77225-UTQC-L/XL	SW77225-UTQC-2X	SW77225-UTQC-3X	SW77225-UTQC-4X
5	SW77225-UT2QCSL-XS	SW77225-UT2QCSL-S/M	SW77225-UT2QCSL-L/XL	SW77225-UT2QCSL-2X	SW77225-UT2QCSL-3X	SW77225-UT2QCSL-4X



SAFEWAZE



ARC FLASH 6' ENERGY ABSORBING LANYARDS

The Arc Flash 6' Energy Absorbing Lanyard is a specialized connection solution providing safe, secure work in arc event rated areas. Built with Mil-Spec flame and heat resistant nylon webbing and Nomex® protective shock cover. Includes dual leg for 100% tie-off, protective label cover and dielectric hooks.



ARC FLASH 6' ENERGY ABSORBING LANYARD

Dual Leg, Dielectric Snap Hooks

SW561-AF-DE

- 1" Nylon webbing
- (3) Dielectric snap hooks
- Nomex® label cover
- Nomex® shock cover
- Dual leg construction
- 40Cal/550F rated
- Capacity 130-310 lb
- Minimum breaking strength 5,000 lb
- Meets ANSI Z359.13, ASTM F887, OSHA 1926.502

ARC FLASH 6' ENERGY ABSORBING LANYARD

Dielectric Snap Hook, Soft Loop

SW560-AF-DE-SE

- 1" Nylon webbing
- (1) Dielectric snap hook
- (1) Soft loop
- Nomex® label cover
- Nomex® shock cover
- Single leg construction
- 40Cal/550F rated
- Capacity 130-310 lb
- Minimum breaking strength 5,000 lb
- Meets ANSI Z359.13, ASTM F887, OSHA 1926.502



ARC FLASH 6' ENERGY ABSORBING LANYARD

Snap Hooks

FS560-AF-AJ

- Adjustable 4'- 6'
- 1" Nylon webbing
- (2) Forged steel snap hooks
- Nomex® label cover
- Nomex® shock cover
- Single leg construction
- 40Cal/550F rated
- Capacity 130-310 lb
- Minimum breaking strength 5,000 lb
- Meets ANSI Z359.13, ASTM F887, OSHA 1926.502

ARC FLASH 6' ENERGY ABSORBING LANYARD

Snap Hook

SW560-AF-DE

- 1" Nylon webbing
- (2) Dielectric snap hooks
- Nomex® label cover
- Nomex® shock cover
- Single leg construction
- 40Cal/550F rated
- Capacity 130-310 lb
- Minimum breaking strength 5,000 lb
- Meets ANSI Z359.13, ASTM F887, OSHA 1926.502



ARC FLASH 6' ENERGY ABSORBING LANYARD

Snap Hooks

FS560-AF

- 1" Nylon webbing
- (2) Forged steel snap hooks
- Nomex® label cover
- Nomex® shock cover
- Single leg construction
- 40Cal/550F rated
- Capacity 130-310 lb
- Minimum breaking strength 5,000 lb
- Meets ANSI Z359.13, ASTM F887, OSHA 1926.502

ARC FLASH 6' ENERGY ABSORBING LANYARD

Snap Hook, Soft Loop

FW560-AF-SE

- 1" Nylon webbing
- (1) Forged steel snap hook
- (1) Soft Loop
- Nomex® label cover
- Nomex® shock cover
- Single leg construction
- 40Cal/550F rated
- Capacity 130-310 lb
- Minimum breaking strength 5,000 lb
- Meets ANSI Z359.13, ASTM F887, OSHA 1926.502



SAFEWAZE



Arc Flash

ARC FLASH 6' ENERGY ABSORBING LANYARDS

The Arc Flash 6' Energy Absorbing Lanyard is a specialized connection solution providing safe, secure work in arc event rated areas. Built with superior flame and heat resistant aramid yarns and Nomex® protective shock cover. Includes dual leg for 100% tie-off, protective label cover and dielectric hooks.



ARC FLASH 6' ENERGY ABSORBING LANYARD

Aramid, Dual Leg, Dielectric Snap Hooks

020-2040

- 1-3/4" Kevlar® aramid webbing
- (3) Dielectric snap hooks
- Nomex® label cover
- Nomex® shock cover
- Dual leg construction
- 40Cal rated
- Capacity 130-310 lb
- Minimum breaking strength 5,000 lb
- Meets ANSI Z359.13, ASTM F887, OSHA 1926.502



ARC FLASH 6' ENERGY ABSORBING LANYARD

Aramid, Dual Leg, Aluminum Rebar Hooks

020-2041

- 1-3/4" Kevlar® aramid webbing
- (1) Forged aluminum snap hooks
- (2) Forged aluminum rebar hooks
- Nomex® label cover
- Nomex® shock cover
- Dual leg construction
- 40Cal/rated
- Capacity 130-310 lb
- Minimum breaking strength 5,000 lb
- Meets ANSI Z359.13, ASTM F887, OSHA 1926.502



ARC FLASH 6' ENERGY ABSORBING LANYARD

020-2042

- 1-3/4" Kevlar® aramid webbing
- (1) Forged steel snap hooks
- (2) Forged steel rebar hooks
- Nomex® label cover
- Nomex® shock cover
- Dual leg construction
- Capacity 130-310 lb
- Minimum breaking strength 5,000 lb
- Meets ANSI Z359.13, ASTM F887, OSHA 1926.502



ARC FLASH 6' ENERGY ABSORBING LANYARD

Aramid, Dual Leg, Aluminum Snap Hooks

020-2043

- 1-3/4" Kevlar® aramid webbing
- (3) Forged aluminum snap hooks
- Nomex® label cover
- Nomex® shock cover
- Dual leg construction
- 40Cal rated
- Capacity 130-310 lb
- Minimum breaking strength 5,000 lb
- Meets ANSI Z359.13, ASTM F887, OSHA 1926.502



ARC FLASH 6' ENERGY ABSORBING LANYARD

Aramid, Dual Leg, Snap Hooks

020-2044

- 1-3/4" Kevlar® aramid webbing
- (3) Forged steel snap hooks
- Nomex® label cover
- Nomex® shock cover
- Dual leg construction
- 40Cal/550F rated
- Capacity 130-310 lb
- Minimum breaking strength 5,000 lb
- Meets ANSI Z359.13, ASTM F887, OSHA 1926.502



ARC FLASH 6' ENERGY ABSORBING LANYARD

Aramid, Snap Hook

020-2045

- 1" Nylon webbing
- (2) Forged steel snap hook
- Nomex® label cover
- Nomex® shock cover
- Single leg construction
- 40Cal/550F rated
- Capacity 130-310 lb
- Minimum breaking strength 5,000 lb
- Meets ANSI Z359.13, ASTM F887, OSHA 1926.502



SAFEWAZE



Arc Flash

LATITUDE PRO ARC FLASH 7' WEB SELF RETRACTING LIFELINES

The Latitude Pro Arc Flash 7' Web Self Retracting Lifelines are built with the same features as our standard Latitude Pro plus Kevlar® webbing and tested to the latest ASTM standard. These are ideal SRLs for use in extreme heat, welding and flash-point environments.



LATITUDE PRO ARC FLASH

LATITUDE PRO ARC FLASH 7' SINGLE WEB SRL-P

Carabiner, Snap Hook

020-5200


- Complete confidence in full, continuous retraction with side payout housing
- Reliable internal braking system eliminates need for external shock pack
- 360/180° attachment point offers full range of motion
- High strength semi-sealed assembly protects internal components from debris to extend product life
- Translucent housing allows easy inspection of webbing, reserve line and pawl assembly
- Trusted Kevlar® webbing and Nomax® flame-resistant label cover
- Minimal exposed webbing protects against UV damage
- All components are Z359.12 compliant



360/180°
Attachment Point



Behind the Web Bracket



Clear Resin Housing



Side Payout Housing



Protective Label Cover



Kevlar® Webbing



LATITUDE PRO ARC FLASH 7' SINGLE WEB TSRL-P

9013, Snap Hook

020-5204

- Complete confidence in full, continuous retraction with side payout housing
- Reliable internal braking system eliminates need for external shock pack
- 360/180° attachment point offers full range of motion
- High strength semi-sealed assembly protects internal components from debris to extend product life
- Translucent housing allows easy inspection of webbing, reserve line and pawl assembly
- Trusted Kevlar® webbing and Nomax® flame-resistant label cover
- Minimal exposed webbing protects against UV damage
- All components are Z359.12 compliant



LATITUDE PRO ARC FLASH 7' DUAL WEB SRL-P

9013 BWB, Snap Hooks

020-5213

- Complete confidence in full, continuous retraction with side payout housing
- Reliable internal braking system eliminates need for external shock pack
- 360/180° attachment point offers full range of motion
- High strength semi-sealed assembly protects internal components from debris to extend product life
- Translucent housing allows easy inspection of webbing, reserve line and pawl assembly
- Trusted Kevlar® webbing and Nomax® flame-resistant label cover
- Minimal exposed webbing protects against UV damage
- Dual hooks to maintain 100% tie-off
- All components are Z359.12 compliant



LATITUDE PRO ARC FLASH 7' DUAL WEB SRL-P
9012 BWB, Snap Hooks
020-5217

- Complete confidence in full, continuous retraction with side payout housing
- Reliable internal braking system eliminates need for external shock pack
- 360/180° attachment point offers full range of motion
- High strength semi-sealed assembly protects internal components from debris to extend product life
- Translucent housing allows easy inspection of webbing, reserve line and pawl assembly
- Trusted Kevlar® webbing and Nomax® flame-resistant label cover
- Minimal exposed webbing protects against UV damage
- All components are Z359.12 compliant



LATITUDE PRO ARC FLASH 7' SINGLE WEB SRL-P
Aramid Soft Loop, DE Snap Hook
022-5308

- Non-conductive soft loop chokes around harness dorsal D-Ring or anchor connection point
- Complete confidence in full, continuous retraction with side payout housing
- Reliable internal braking system eliminates need for external shock pack
- 360/180° attachment point offers full range of motion
- High strength semi-sealed assembly protects internal components from debris to extend product life
- Translucent housing allows easy inspection of webbing, reserve line and pawl assembly
- Trusted Kevlar® webbing and Nomax® flame-resistant label cover
- Minimal exposed webbing protects against UV damage
- All components are Z359.12 compliant



LATITUDE PRO ARC FLASH 7' SINGLE WEB SRL-P
13" Aramid Extension with Aluminum Snap Hook
Aluminum Captive Eye Carabiner
022-5309

- 13" Aramid extender prevents current from traveling between attachment point and SRL housing
- Complete confidence in full, continuous retraction with side payout housing
- Reliable internal braking system eliminates need for external shock pack
- 360/180° attachment point offers full range of motion
- High strength semi-sealed assembly protects internal components from debris to extend product life
- Translucent housing allows easy inspection of webbing, reserve line and pawl assembly
- Trusted Kevlar® webbing and Nomex® flame-resistant label cover
- Minimal exposed webbing protects against UV damage
- All components are Z359.12 compliant



LATITUDE PRO ARC FLASH 7' SINGLE WEB SRL-P
18"- 22" Adjustable Aramid Extension
Aluminum Captive Eye Carabiners
022-5310

- 18"- 22" Aramid extender prevents current from traveling between the attachment point and SRL housing
- Complete confidence in full, continuous retraction with side payout housing
- Reliable internal braking system eliminates need for external shock pack
- 360/180° attachment point offers full range of motion
- High strength semi-sealed assembly protects internal components from debris to extend product life
- Translucent housing allows easy inspection of webbing, reserve line and pawl assembly
- Trusted Kevlar® webbing and Nomax® flame-resistant label cover
- Minimal exposed webbing protects against UV damage
- Dual hooks to maintain 100% tie-off
- All components are Z359.12 compliant



	Steel Carabiner	9013 Behind the Web Bracket	9013 Behind the Web Bracket	9012 Behind the Web Bracket
Steel Snap Hooks	020-5200	020-5204	020-5213	020-5217
Aluminum Snap Hooks	020-5202	020-5206	020-5215	020-5219
Steel Rebar Hooks	020-5201	020-5205	020-5214	020-5218
Aluminum Rebar Hooks	020-5203	020-5207	020-5216	020-5220
Dielectric Snap Hooks	-	020-5208	020-5221	-



PROTECTIVE INDUSTRIAL PRODUCTS

NOVAX® RUBBER INSULATING GLOVES

Straight Cuff



155-2-14



147-1-14



150-2-14















150-2-14

NOVAX® Straight Cuff

Style Number	Class	Color	Length	Sizes	Style Number	Class	Color	Length	Sizes
147-00-11	00	Orange	11"	7 - 12	155-1-14	1	Black/Orange	14"	7 - 12
150-00-11	00	Black	11"	7 - 12	147-2-14	2	Orange	14"	7 - 12
150-00-14	00	Black	14"	7 - 12	150-2-14	2	Black	14"	7 - 12
170-00-11	00	Yellow	11"	7 - 12	152-2-18	2	Black/Yellow	16"	7 - 12
170-00-14	00	Yellow	14"	7 - 12	153-2-14	2	Black/Yellow	18"	7 - 12
147-0-11	0	Orange	11"	7 - 12	155-2-14	2	Red	14"	7 - 12
150-0-11	0	Black	11"	7 - 12	155-2-16	2	Black/Orange	14"	7 - 12
150-0-14	0	Black	14"	7 - 12	155-2-18	2	Black/Orange	16"	7 - 12
153-0-11	0	Red	11"	8 - 12	170-2-14	2	Black/Orange	18"	8 - 12
155-0-11	0	Black/Orange	11"	7 - 12	155-2-16	2	Yellow	14"	7 - 12
170-0-11	0	Yellow	11"	7 - 12	155-3-16	3	Black/Orange	16"	7 - 12
170-0-14	0	Yellow	14"	7 - 12	155-3-18	3	Black/Orange	18"	7 - 12
147-1-14	1	Orange	14"	7 - 12	155-4-16	4	Black/Orange	18"	7 - 12
150-1-14	1	Black	14"	7 - 12	155-4-19	4	Black/Orange	18"	7 - 12
153-1-14	1	Red	14"	7 - 12					

Labeling

Class Color	Novak Glove Label	Test AC Volts	Use AC Volts	Use DC Volts
		2,500	500	750
		5,000	1,000	1,500
		10,000	7,500	11,250
		20,000	17,000	25,500
		30,000	25,500	39,750
		40,000	36,000	54,000

Standards & Regulations

OSHA

29CFR part 1910 (Occupational Safety and Health Standards)

ASTM

- ASTM D120-14a (Rubber Insulating Gloves)
- ASTM F496-14a (In-Service Care of Insulating Gloves and Sleeves)
- ASTM F696-06 (Leather Protectors for Rubber Insulating Gloves and Mittens)
- ASTM F1236-16 (Visual Inspection of Electrical Protective Rubber Products)
- ASTM D1051-14a (Rubber Insulating Sleeves)
- ASTM D1048-14 (Rubber Insulating Blankets)

NFPA

- National Electric Safety Code
- NFPA 70E (Electrical Safety in the Workplace - General Workplaces)



PROTECTIVE INDUSTRIAL PRODUCTS

NOVAX® RUBBER INSULATING GLOVES Bell Cuff & Contour



161-2-16



150-4-18



162-2-18



152-2-18













NOVAX® Straight Cuff

Style Number	Class	Color	Length	Sizes
154-2-16	2	Black/Yellow	16"	8 - 12
154-2-18	2	Black/Yellow	18"	8 - 12
159-2-16	2	Black/Orange	16"	9- 12
159-2-18	2	Black/Orange	18"	9- 12
159-3-16	3	Black/Orange	16"	9- 12
159-3-18	3	Black/Orange	18"	9- 12
159-4-16	4	Black/Orange	16"	9- 12
159-4-18	4	Black/Orange	18"	9- 12
159-4-18	2	Black/Red	16"	9- 12
161-2-18	2	Black/Red	18"	9- 12
161-3-16	3	Black/Red	16"	9 - 11

NOVAX® Contour

Style Number	Class	Color	Length	Sizes
151-2-18	2	Black/Yellow	18"	8 - 12
158-2-18	2	Black/Orange	18"	8 - 12
162-2-18	2	Black/Red	18"	8 - 12
151-3-18	3	Black/Yellow	18"	9- 12
158-3-18	3	Black/Orange	18"	9- 12
151-4-18	4	Black/Yellow	18"	9- 12
158-4-18	4	Black/Orange	18"	9- 12
162-4-18	4	Black/Red	18"	9- 11

Labeling

Class Color	Novak Glove Label	Test AC Volts	Use AC Volts	Use DC Volts
		2,500	500	750
		5,000	1,000	1,500
		10,000	7,500	11,250
		20,000	17,000	25,500
		30,000	25,500	39,750
		40,000	36,000	54,000

Standards & Regulations

OSHA

29CFR part 1910 (Occupational Safety and Health Standards)

ASTM

- ASTM D120-14a (Rubber Insulating Gloves)
- ASTM F496-14a (In-Service Care of Insulating Gloves and Sleeves)
- ASTM F696-06 (Leather Protectors for Rubber Insulating Gloves and Mittens)
- ASTM F1236-16 (Visual Inspection of Electrical Protective Rubber Products)
- ASTM D1051-14a (Rubber Insulating Sleeves)
- ASTM D1048-14 (Rubber Insulating Blankets)

NFPA

- National Electric Safety Code
- NFPA 70E (Electrical Safety in the Workplace - General Workplaces)



PIP®

Regular Grade Top Grain Cowhide Leather Drivers Glove - Straight Thumb

- Top Grain Cowhide leather construction provides comfort, durability, excellent abrasion resistance, and breathability
- Top Grain leather is smooth, provides durability and dexterity
- Drivers gloves feature slip-on styling to provide good fit and comfort
- Straight thumb increases comfort in closed-fisted work
- Elastic closure sewn inside glove for safety and comfort
- Color coded hem for easy size identification

Applications

- General Applications
- Construction Applications
- Roofing
- Farming
- Utility Work
- Roping

Care Instructions

Do Not Wash!



Performance Data

ANSI Cut Level	--
ANSI Puncture Level	--
EN388	--

Technical Data

Color	Sizes	Quantity	Case Dimensions	Case Weight	Hide	Grade	Cuff	Stitching	Thumb	Certifications
Natural	S-2XL	Bulk Pack	24.80" x 10.63" x 11.81"	46.30 lb	Top Grain Cowhide	Regular	Slip-on	Nylon	Straight	Chromium VI Free

Part No.	Color	Size
68-103/S	Natural	S
68-103/M	Natural	M
68-103/L	Natural	L
68-103/XL	Natural	XL
68-103/XXL	Natural	2XL



PROTECTIVE INDUSTRIAL PRODUCTS

BOSS®

Top Grain Sheepskin Leather Drivers glove with Impact Protection and Aramid Blend Lining

- Sheepskin leather palm and back is more supple than cowhide so they're broken in from the start
- Para-Aramid lining offers comfort, enhanced cut protection and good heat dispersion
- Kevlar® yarn for stitching is heavy-duty
- Thermo Plastic Rubber (TPR) back-of-hand impact resistance to knuckles and fingers by dispersing impact force energy away from the bone, without sacrificing dexterity
- Drivers gloves feature slip-on styling to provide good fit and comfort
- Keystone thumb is ergonomic, reduces hand fatigue, offers superior dexterity and durability

Applications

- Cut Resistance with Light Heat Protection
- Automotive Applications
- Glass Operations

Care Instructions

Do Not Wash!



Performance Data	
ANSI Cut Level	A4
ANSI Abrasion Level	--
ANSI Puncture Level	4
ANSI Impact Level	2
ANSI Contact Heat Level	--
EN388	2X22DP
ASTM F1358 Vertical Flame Level	--
EN407	--

Technical Data

Color	Sizes	Quantity	Case Dimensions	Case Weight	Liner Material	Hide	Cuff	Impact Protection
Natural	S-3XL	72 Pair/Case	21.02" x 15.98" x 15.00"	48.24 lb	Aramid, Polyester	Top Grain Sheepskin	Slip-on	Finger, Thumb Back of Hand

Part No.	Color	Size
9120/S	Natural	S
9120/M	Natural	M
9120/L	Natural	L
9120/XL	Natural	XL
9120/2XL	Natural	2XL
9120/3XL	Natural	3XL



BOSS®

Top Grain Goatskin Leather Drivers Glove with Hi-Vis Impact Protection and DuPont™ Kevlar® Blend Lining

- Top Grain Goatskin leather construction is the softest, most abrasion-resistant leather and is highly recommended for applications requiring tactile sensitivity
- Top Grain leather is smooth, provides durability and dexterity
- Kevlar® blended fiber liner on palm for superior cut protection
- Thermo Plastic Rubber (TPR) back-of-hand impact resistance to knuckles and fingers by dispersing impact force energy away from the bone, without sacrificing dexterity
- ANSI Level 4 Puncture Resistance
- Hook & loop closure for easy on/o and a secure fit

Applications

- Cut Resistance with Light Heat Protection
- Automotive Applications
- Glass Operations

Care Instructions

Do Not Wash!



Performance Data	
ANSI Cut Level	A7
ANSI Puncture Level	--
ANSI Puncture Level	4
ANSI Impact Level	1
ANSI Contact Heat Level	--
ANSI Contact Heat Level	--
EN 388	3X44FP
ASTM F1358 Vertical Flame Level	--
EN 407	--

Technical Data

Color	Sizes	Quantity	Case Dimensions	Case Weight	Liner Material	Hide	Cuff	Impact Protection
Natural	S-3XL	72 Pair/Case	28.35" x 11.74" x 15.08"	40.57 lb	Kevlar	Top Grain Goatskin	Slip-on	Finger, Thumb Back of Hand

Part No.	Color	Size
9916/S	Natural	S
9916/M	Natural	M
9916/L	Natural	L
9916/XL	Natural	XL
9916/2XL	Natural	2XL
9916/3XL	Natural	3XL



G-Tek® PolyKor®

Seamless Knit PolyKor® Blended Glove with Polyurethane Coated Flat Grip on Palm & Fingers

- Seamless construction offers increased comfort and breathability
- PolyKor® blended shell is lightweight and provides excellent dexterity, tactile sensitivity, and cut resistance
- Polyurethane coatings take on the surface properties of the glove liner providing a tactile grip in dry and slightly oily conditions, ideal for applications that require dexterity for precise handling
- Knit Wrist helps prevent dirt and debris from entering the glove
- Color coded hems for easy size identification
- Washable, resistant to chemicals, water, and ultraviolet light

Applications

- Thin Coating, Good Grip for High Dexterity Handling
- Maintenance and Repair Operations
- Handling, Assembly and Sorting of Small to Medium Parts and Materials
- Shipping, Receiving and Packaging

Care Instructions

Machine Wash, Water Temp 40°, Do Not Bleach, Tumble Dry, Low Heat



Performance Data	
ANSI Cut Level	A4
ANSI Abrasion Level	4
ANSI Puncture Level	4
ANSI Impact Level	--
ANSI Contact Heat Level	--
EN388	4X43DX
ASTM F1358 Vertical Flame Level	--
EN407	--

Technical Data

Color	Sizes	Quantity	Case Dimensions	Case Weight	Liner Material	Coating	Coating Coverage	Grip	Gauge	Certifications
Gray	XXS-2XL	6 Dozen/Case	14.96" x 11.81" x 9.84"	12.13 lb	PolyKor®	Polyurethane	Palm & Fingers	Flat	13	Silicon Free

Part No.	Color	Size
16-560/XXS	Gray	XXS
16-560/XS	Gray	XS
16-560/S	Gray	S
16-560/M	Gray	M
16-560/L	Gray	L
16-560/XL	Gray	XL
16-560/XXL	Gray	2XL



G-Tek® PolyKor®

Industry Grade Seamless Knit PolyKor® Blended Glove with Polyurethane Coated Flat Grip on Palm & Fingers

- Seamless construction offers increased comfort and breathability
- PolyKor® blended shell is lightweight and provides excellent dexterity, tactile sensitivity, and cut resistance
- Polyurethane coatings take on the surface properties of the glove liner providing a tactile grip in dry and slightly oily conditions, ideal for applications that require dexterity for precise handling
- Knit Wrist helps prevent dirt and debris from entering the glove
- Color coded hems for easy size identification
- 100% Silicone Free

Applications

- Thin Coating, Good Grip for High Dexterity Handling
- Maintenance and Repair Operations
- Handling, Assembly and Sorting of Small to Medium Parts and Materials
- Shipping, Receiving and Packaging

Care Instructions

Machine Wash, Water Temp 40°, Do Not Bleach, Tumble Dry, Low Heat

Performance Data	
ANSI Cut Level	A4
ANSI Abrasion Level	3
ANSI Puncture Level	2
ANSI Impact Level	--
ANSI Contact Heat Level	--
EN388	4X41DX
ASTM F1358 Vertical Flame Level	--
EN407	--



Technical Data

Color	Sizes	Quantity	Case Dimensions	Case Weight	Liner Material	Coating	Coating Coverage	Grip	Gauge	Certifications
Gray	XXS-2XL	6 Dozen/Case	14.96" x 11.81" x 9.84"	12.13 lb	PolyKor®	Polyurethane	Palm & Fingers	Flat	13	Silicon Free

Part No.	Color	Size
16-564/XXS	Gray	XXS
16-564/XS	Gray	XS
16-564/S	Gray	S
16-564/M	Gray	M
16-564/L	Gray	L
16-564/XL	Gray	XL
16-564/XXL	Gray	2XL



G-Tek® PolyKor®

Seamless Knit PolyKor® Blended Glove with Double-Dipped Nitrile Coated Microsurface Grip on Full Hand

- Seamless construction offers increased comfort and breathability
- PolyKor® blended shell is lightweight and provides excellent dexterity, tactile sensitivity, and cut resistance
- Nitrile Microsurface coatings are impermeable providing an elevated grip in dry and oily conditions, infused with thousands of tiny suction cup pockets that create a vacuum effect that dispenses fluids away on contact
- Microsurface nitrile palm provides excellent grip in dry, wet & oily conditions
- Double-Dipped nitrile palm provides excellent grip in dry, wet & oily conditions
- Knit Wrists helps prevent dirt and debris from entering glove

Applications

- Secure Dry Grip and Oil Resistant
- Handling and Assembly of Medium to Large Parts and Materials
- Metal Fabrication
- Mechanical Equipment Maintenance and Repair
- Heavy to Medium Fastening and Anchoring

Care Instructions

Machine Wash, Water Temp 40°, Do Not Bleach, Tumble Dry, Low Heat

Performance Data	
ANSI Cut Level	A4
ANSI Abrasion Level	3
ANSI Puncture Level	5
ANSI Impact Level	--
ANSI Contact Heat Level	--
EN388	4X43DX
ASTM F1358 Vertical Flame Level	--
EN407	--



Technical Data

Color	Sizes	Quantity	Case Dimensions	Case Weight	Liner Material	Coating	Coating Coverage	Grip	Gauge	Certifications
Blue	XS-2XL	6 Dozen/Case	16.54" x 11.81" x 12.60"	22.27 lb	PolyKor®	Nitrile	Full Hand	Microsurface	13	Silicon Free

Part No.	Color	Size
16-CUT229MS/XS	Blue	XS
16-CUT229MS/S	Blue	S
16-CUT229MS/M	Blue	M
16-CUT229MS/L	Blue	L
16-CUT229MS/XL	Blue	XL
16-CUT229MS/XXL	Blue	XXL



SVE1 ECONOMY TYPE R CLASS 2 SAFETY VEST

The Radwear SVE1 provides compliant protection at an economical price and meets ANSI/ISEA 107 standards. The high visibility, 100% polyester mesh material with a zipper closure provides a lightweight, comfortable fit with extra protection in bright and low light environments.

Mesh	
Green	Orange
SVE1-2ZGM-S/M	SVE1-270M-S/M
SVE1-2ZGM-L/XL	SVE1-270M-L/XL
SVE1-2ZGM-2X/3X	SVE1-270M-2X/3X
SVE1-2ZGM-4X/5X	SVE1-270M-4X/5X



Features

- Zipper Closure
- 2" Silver Tape Reflective Material
- 1 Horizontal Stripe
- 100% Polyester Mesh

Colors

- High-Visibility Green
- High-Visibility Orange

Available Sizes	S/M	L/XL	2X/3X	4X/5X
Chest Width Measurement (Flat)	17	18	19	20
Vest Chest Circumference	24	27	28	30
Length From High Point of Shoulder	26	27	28	30



25 WASH MAX!

SV2 ECONOMY TYPE R CLASS 2 SOLID SAFETY VEST

Radians SV2 Economy Type R Class 2 Safety Vest offers compliant protection at an economical price. Excellent choice for extreme work environments, like asphalt paving, that greatly reduce the useful life of a vest, or protection for short-term labor.

Solid		Mesh	
Green	Orange	Green	Orange
SV2GSS	SV2OSS	SVG2MS	SV2OMS
SV2GSM	SV2OSM	SVG2MM	SV2OMM
SV2GSSL	SV2OSL	SVG2ML	SV2OML
SV2GSXL	SV2OXL	SVG2MXL	SV2OML
SV2GS2X	SV2O2X	SV2GM2X	SV2OM2X
SV2GS3X	SV2O3X	SV2GM3X	SV2OM3X
SV2GS4X	SV2O4X	SV2GM4X	SV2OM4X
SV2GS5X	SV2O5X	SV2GM5X	SV2OM5X



Features

- Hook & Loop Closure
- 2" Silver Refl. Material
- 1 Horizontal Stripe
- 100% Polyester Mesh
- 1 Upper left Front Chest Pocket
- 1 Lower Right Inside Pocket

Available Sizes	S	M	L	XL	2X	3X	4X	5X
Body Chest Circumference	34-36	38-40	42-44	46-48	50-52	54-56	58-60	62-64
Vest Chest Circumference	41	50	52	56	60	64	68	72
Length From High Point of Shoulder	25	26	26	27	28	29	30	31



25 WASH MAX!



SV22-3 ECONOMY TYPE R CLASS 3 SAFETY VEST w/TWO-TONE TRIM

The Radians SV22-3 Economy Type R Class 3 with Two-Tone Trim is compliant protection at an economical price. Excellent choice for extreme work environments like asphalt paving that greatly reduce the useful life of a vest, or protection for short-term labor. Reflective stripes on contrasting trim make workers much more noticeable in low light and broad daylight. Great for roadway construction workers, utility workers, survey crews, emergency response personnel.

Mesh	
Green	Orange
SV22-3ZGMS	SV22-3ZOMS
SV22-3ZGMM	SV22-3ZOMM
SV22-3ZGML	SV22-3ZOML
SV22-3ZGMXL	SV22-3ZOMXL
SV22-3ZGM2X	SV22-3ZOM2X
SV22-3ZGM3X	SV22-3ZOM3X
SV22-3ZGM4X	SV22-3ZOM4X
SV22-3ZGM5X	SV22-3ZOM5X

Available Sizes
S, M, L, XL, 2X, 3X, 4X, 5X

Features

- Zipper Closure
- 2" Silver Tape Reflective Material
- 1 Horizontal Stripe
- Contrasting Trim Detail
- 1 Upper left Front Chest Pocket
- 1 Lower Right Inside Pocket

Colors

- High-Visibility Green
- High-Visibility Orange



CUSTOM IMPRINTING

Left Chest Pocket
Back Center

25 WASH MAX!

SV3 ECONOMY MESH TYPE R CLASS 3 SAFETY VEST

Radians SV3 is an economy Type R class 3 all mesh vest available in a combination of sizes. The vest is made with a single horizontal stripe, zipper front closure, one upper front radio pocket, and two inside open pockets. This vest is intended for warm weather, high visibility situations where class 3 vests are required.

Mesh
Green
SV3ZGM-S/M
SV3ZGM-L/XL
SV3ZGM-2X/3X
SV3ZGM-4X/5X

Available Sizes
S, M, L, XL, 2X, 3X, 4X, 5X



Features

- Zipper Closure
- 2" Silver Tape Reflective Material
- 1 Horizontal Stripe
- 100% Polyester Mesh
- 1 Upper left Front Chest Pocket
- 1 Upper Inside Pocket
- 1 Lower Inside Pocket

Colors

- High-Visibility Green



CUSTOM IMPRINTING

Left Chest Pocket
Back Center



SV97 ECONOMY MESH FR CLASS 2 SAFETY VEST

The SV97E is a custom, made in the USA, modacrylic mesh FR safety vest. Manufactured in our North Carolina facility, the SV97E is available on a build to order basis with a lead time of approximately 2 weeks for orders under 300 pieces.

Mesh
Green
SV97E-2VGM-M
SV97E-2VGM-L
SV97E-2VGM-XL
SV97E-2VGM-2X
SV97E-2VGM-3X
SV97E-2VGM-4X
SV97E-2VGM-5X
Available Sizes
M, L, XL, 2X, 3X, 4X, 5X
25 WASH MAX!



Features

- Zipper Closure
- 2" Silver Tape Reflective Material
- 1 Horizontal Stripe
- 100% Polyester Mesh

Specifications

- 4.6 Cal ATPV
- NFPA 70E Cat 1
- Meets ASTM 1506
- 5.8 oz Modacrylic Mesh



CUSTOM IMPRINTING



SV97 ECONOMY MESH FR CLASS 3 SAFETY VEST

Radians SV3 is an economy Type R class 3 all mesh vest available in a combination of sizes. The vest is made with a single horizontal stripe, zipper front closure, one upper front radio pocket, and two inside open pockets. This vest is intended for warm weather, high visibility situations where class 3 vests are required.

Mesh
Green
SV97E-3VGMFR-M
SV97E-3VGMFR-L
SV97E-3VGMFR-XL
SV97E-3VGMFR-2X
SV97E-3VGMFR-3X
SV97E-3VGMFR-4X
SV97E-3VGMFR-5X
Available Sizes
M, L, XL, 2X, 3X, 4X, 5X
25 WASH MAX!



Features

- Zipper Closure
- 2" Silver Tape Reflective Material
- 1 Horizontal Stripe
- 100% Polyester Mesh

Specifications

- 4.6 Cal ATPV
- NFPA 70E Cat 1
- Meets ASTM 1506
- 5.8 oz Modacrylic Mesh



CUSTOM IMPRINTING





ST11 CLASS 2 HIGH VISIBILITY T-SHIRT W/MAX-DRI™

Radians ST21 Class 3 Long Sleeve Safety T-Shirt is made with Max-Dri™ which is an arid Birdseye Moisture Wicking Mesh allowing for maximum breathability, without compromising durability. The stripes are adhered by heat transfer rather than sewn on, making the safety T-shirt wear much more like a regular T-shirt. The wicking properties improve hot weather comfort making it feel much cooler.

Mesh	
Green	Orange
ST11-2PGS-M	ST11-2POS-M
ST11-2PGS-L	ST11-2POS-L
ST11-2PGS-XL	ST11-2POS-XL
ST11-2PGS-2X	ST11-2POS-2X
ST11-2PGS-3X	ST11-2POS-3X
ST11-2PGS-4X	ST11-2POS-4X
ST11-2PGS-5X	ST11-2POS-5X



Features

- 2" Premium Heat Transferred, Stretchable Reflective Tape
- 1 Horizontal Stripes
- 1 Upper left Front Chest Pocket

Colors

- High-Visibility Green
- High-Visibility Orange



CUSTOM IMPRINTING
Left Chest Pocket
Back Center

Available Sizes	S	M	L	XL	2X	3X	4X	5X
Body Chest Circumference	15.75	16.75	17.75	18.75	19.75	21	22.25	23.5
Vest Chest Circumference	31.5	33.5	35.5	35.7	39.5	42	44.5	47
Length From High Point of Shoulder	28	29	30	31	32	33	33	35

ST21 CLASS 3 LONG SLEEVE T-SHIRT W/MAX-DRI™

Radians ST21 Class 3 Long Sleeve Safety T-Shirt is made with Max-Dri™ which is an arid Birdseye Moisture Wicking Mesh allowing for maximum breathability, without compromising durability. The stripes are adhered by heat transfer rather than sewn on, making the safety T-shirt wear much more like a regular T-shirt. The wicking properties improve hot weather comfort making it feel much cooler.

Mesh	
Green	Orange
ST21-3PGS-M	ST21-3POS-M
ST21-3PGS-L	ST21-3POS-L
ST21-3PGS-XL	ST21-3POS-XL
ST21-3PGS-2X	ST21-3POS-2X
ST21-3PGS-3X	ST21-3POS-3X
ST21-3PGS-4X	ST21-3POS-4X
ST21-3PGS-5X	ST21-3POS-5X



Features

- 2" Premium Heat Transferred, Stretchable Reflective Tape
- 1 Horizontal Stripes
- Sleeve Stripes
- 1 Upper left Front Chest Pocket

Colors

- High-Visibility Green
- High-Visibility Orange



CUSTOM IMPRINTING
Left Chest Pocket
Back Center

Available Sizes	S	M	L	XL	2X	3X	4X	5X
Body Chest Circumference	15.75	16.75	17.75	18.75	19.75	21	22.25	23.5
Vest Chest Circumference	31.5	33.5	35.5	35.7	39.5	42	44.5	47
Length From High Point of Shoulder	28	29	30	31	32	33	33	35



SJ01B-3 CLASS 3 COLOR BLOCKED HOODED SWEATSHIRT

Radians SJ01B-3 Type R, Class 3, Long Sleeve Hooded Sweatshirt with zipper closure offers superior warmth while keeping you visible. Color blocking at the bottom conceals dirt.

Mesh	
Green	Orange
SJ01B-3ZGS-M	SJ01B-3ZOS-M
SJ01B-3ZGS-L	SJ01B-3ZOS-M
SJ01B-3ZGS-XL	SJ01B-3ZOS-M
SJ01B-3ZGS-2X	SJ01B-3ZOS-M
SJ01B-3ZGS-3X	SJ01B-3ZOS-M
SJ01B-3ZGS-4X	SJ01B-3ZOS-M
SJ01B-3ZGS-5X	SJ01B-3ZOS-M

25 WASH MAX!



Features

- Zipper Closure
- 2" Silver Tape Reflective Material
- 1 Horizontal Stripe, 2 on Sleeves
- 2 Lower Pouch Pockets
- Low Pilling Fleece
- Birds-Eye Mesh Lined Hood

Colors

- High-Visibility Green
- High-Visibility Orange



CUSTOM IMPRINTING

Left Chest
Back Center

Available Sizes	M	L	XL	2X	3X	4X	5X
Chest Width Measurement (Flat)	23	25	27	29	31	33	35
Chest Circumference	46	50	54	58	62	66	70
Length From High Point of Shoulder	28	30	30	31	32	32	34

SJ11QB CLASS 3 HIGH VISIBILITY WEATHERPROOF BOMBER JACKET W/QUILTED LINER

Radians SJ11QB Class 3 weather proof Bomber Jacket with a quilted liner makes it very easy to slip on and off over other fleece or other warm outwear.

Mesh	
Green	Orange
SJ11QB-3ZGS-M	SJ11QB-3ZOS-M
SJ11QB-3ZGS-L	SJ11QB-3ZOS-L
SJ11QB-3ZGS-XL	SJ11QB-3ZOS-XL
SJ11QB-3ZGS-2X	SJ11QB-3ZOS-2X
SJ11QB-3ZGS-3X	SJ11QB-3ZOS-3X
SJ11QB-3ZGS-4X	SJ11QB-3ZOS-4X
SJ11QB-3ZGS-5X	SJ11QB-3ZOS-5X

25 WASH MAX!



Features

- Color Blocked Bottom
- Dual Mic Tabs
- Concealed Attached Hood
- Elastic Waistband and Wrist Cuff
- Zipper Closure
- 2" Silver Tape Reflective Material
- 1 Horizontal Strip, 2 on Sleeves
- Upper Front & Lower Front Pockets
- Inside - Open Chest Pocket

Colors

- High-Visibility Green
- High-Visibility Orange



CUSTOM IMPRINTING

Left Chest Pocket
Back Center

Available Sizes	S	M	L	XL	2X	3X	4X	5X
Body Chest Circumference	34-36	38-40	42-44	46-48	50-52	54-56	58-60	62-64
Jacket Chest Circumference	46	50	54	58	62	66	70	74
Length From High Point of Shoulder	27.5	28.5	29.5	30.5	31.5	32.5	33.5	34.5



SJ210B THREE-IN-ONE DELUXE HIGH VISIBILITY BOMBER JACKET

Radians SJ210B Three-in-One Deluxe Bomber Jacket with black bottom has a zip out fleece jacket, concealed attached hood, elasticized waistband and several inner and outer pockets. Safety jacket has 2" silver reflective tape for high visibility.

Mesh	
Green	Orange
SJ01B-3ZGS-M	SJ01B-3ZOS-M
SJ01B-3ZGS-L	SJ01B-3ZOS-M
SJ01B-3ZGS-XL	SJ01B-3ZOS-M
SJ01B-3ZGS-2X	SJ01B-3ZOS-M
SJ01B-3ZGS-3X	SJ01B-3ZOS-M
SJ01B-3ZGS-4X	SJ01B-3ZOS-M
SJ01B-3ZGS-5X	SJ01B-3ZOS-M



Features

- Zip Out Removable Fleece Jacket
- Fleece Jacket Sleeves are lined for easy on and off
- PU Coated Oxford Polyester Weather Proof Shell
- Clear, Chest Badge Holder
- Concealed Attached Hood
- Dual Mic Tabs
- Elasticized Waistband and Wrist Cuff with Closure
- 2" Silver Reflective Material Tape
- Cell Phone/Radio Chest Pocket



REMOVABLE FLEECE JACKET!

Colors

- High-Visibility Green
- High-Visibility Orange

25 WASH MAX!

Available Sizes	S	M	L	XL	2X	3X	4X	5X
Body Chest Circumference	34-36	38-40	42-44	46-48	50-52	54-56	58-60	62-64
Jacket Chest Circumference	-	52	56	60	64	68	72	76
Length From High Point of Shoulder	-	29	29.5	31	32	33	34	35



CUSTOM IMPRINTING
Left Chest
Back Center

SJ610B WEATHERPROOF PARKA W/ZIP-OUT REVERSIBLE BOMBER JACKET

The SJ610B is a feature-packed garment designed for functionality and convenience in multiple seasons! Wind and water-resistant, this coat is made up of an outer parka and a reversible bomber with zip-off sleeves. The parka and bomber are Type R Class 3 compliant and the vest is Type R Class 2 compliant.

Mesh
Green
SJ60B-3ZGS-S
SJ60B-3ZGS-M
SJ60B-3ZGS-L
SJ60B-3ZGS-XL
SJ60B-3ZGS-2X
SJ60B-3ZGS-3X
SJ60B-3ZGS-4X
SJ60B-3ZGS-5X

Features

- Color Blocked Bottom
- Dual Mic Tabs
- Removable Stowable Hood
- Inner Rib Knit Cuffs
- Zipper Closure
- 2" Silver Tape Reflective Material w/Contrasting Overlay
- 1 Horizontal Stripe
- Upper Front, Upper Right Chest Pockets
- 2 Lower Flap Covered Welt Pockets
- Inside, 2 Upper Open Pockets
- 300 PU Coated Oxford Polyester Outer
- Parka Lining: Black Quilted taffeta, 160gsm
- Bomber Black Side, Black Peached Polyester Coated TPU 120gsm



REVERSIBLE ZIP-OUT BOMBER (WITH REMOVABLE SLEEVES)



Colors

- High-Visibility Green

25 WASH MAX!

Available Sizes	S	M	L	XL	2X	3X	4X	5X
Body Chest Circumference	24	26	28	30	32	34	36	38
Length From High Point of Shoulder	32	33	34	34.75	35.5	36.25	37	37.75



8" AXIAL AC PLASTIC MIN-PACK BLOWER

This high output blower's compact design stores ducting inside the blower housing for an all-in-one unit for ease of operation, transportation, and storage! The "safety orange" colored plastic housing is durable, lightweight, corrosion, UV, and chemical resistant with a molded-in carry handle for increased portability. Available with either 15' or 25' of ducting.



Construction

- Polyethylene Housing
- Lightweight, corrosion-, UV- and chemical resistant
- Super quiet, in "safety orange"
- Carry handle molded into blower and canister housing
- Steel powder coated grill
- A separate 12" duct can be attached to the intake side of the blower to draw

Ducting

- Retractable, non-collapsible design
- Single ply, PVC coated vinyl and polyester materials, temperature resistant up to 180° F (82.2° C)
- Yellow color with black wear-strip and integrated nylon attachment strap
- Class 1 hard drawn spring steel wire helix that meets ASTM 227 specs

Motor

HP	Voltage/Hz	RPM	Amps	Fan	Cord	Plug
1/3	115V-230V AC, 50/60Hz Single Phase, All World Motor	2,850-3,350	1.5A-0.8A (50 Hz) / 1.9A-1.0A (60Hz)	9-Blade Polypropylene Fan	6'	NEMA 5-16PT

Part No.	Blower Dimensions	Flow Rates			Weight
		Straight	One 90° Bend	Two 90° Bends	
9532-15	17-1/2" L x 11-1/4" W x 13-1/2" H	791 CFM (1343 m ³ /hr)	703 CFM (1194 m ³ /hr)	621 CFM (1055 m ³ /hr)	19.4 lb
*9532-15E	17-1/2" L x 11-1/4" W x 13-1/2" H	791 CFM (1343 m ³ /hr)	703 CFM (1194 m ³ /hr)	621 CFM (1055 m ³ /hr)	19.4 lb
9532-25	17-1/2" L x 11-1/4" W x 13-1/2" H	760 CFM (1291 m ³ /hr)	674 CFM (1145 m ³ /hr)	602 CFM (1022 m ³ /hr)	23.2 lb
*9532-25E	17-1/2" L x 11-1/4" W x 13-1/2" H	760 CFM (1291 m ³ /hr)	674 CFM (1145 m ³ /hr)	602 CFM (1022 m ³ /hr)	23.2 lb

*E version blowers are 220V, 50 Hz

12" AXIAL AC PLASTIC BLOWER/W CANISTER & DUCTING

High output from a compact axial blower, designed for easy use and storage without sacrificing airflow. Available as blower only or complete unit with 15' or 25' of ducting and storage canister. Canister attaches to intake or output of blower for suction or ventilation. Certified to CSA Standard C22.2 No.113.



Construction

- Polyethylene Housing and canister assembly
- Lightweight, corrosion-, UV- and chemical resistant
- Super quiet, in "safety orange"
- Carry handle molded into blower and canister housing
- Steel powder coated grill

Ducting

- Retractable, non-collapsible design, single ply
- PVC coated vinyl and polyester materials
- Yellow color with black weather strip and integrated nylon attachment strap
- Spring steel wire helix

Motor

HP	Voltage/Hz	RPM	Amps	Fan	Cord	Plug
1	115V-230V AC, 50/60Hz Single Phase	2,800-3400	11A-5.5A (50 Hz) / 10A-5A (60Hz)	6-Blade Polypropylene Fan	15'	NEMA 5-15PT

Part No.	Blower Dimensions	Flow Rates			Weight
		Free Air	One 90° Bend	Two 90° Bends	
9543	13" L x 16" W x 17" H	1842 CFM (3129.57 m ³ /hr)	1004 CFM (1705.8 m ³ /hr)	933 CFM (1584.17 m ³ /hr)	28 lb
9543-15	27" L x 16" W x 17" H	1842 CFM (3129.57 m ³ /hr)	1004 CFM (1705.8 m ³ /hr)	933 CFM (1584.17 m ³ /hr)	43 lb
9543-25	27" L x 16" W x 17" H	1842 CFM (3129.57 m ³ /hr)	1004 CFM (1705.8 m ³ /hr)	933 CFM (1584.17 m ³ /hr)	49 lb



MANHOLE GUARDRAIL

The Manhole Guardrail* is designed as a simple one-piece construction that offers easy, no-tools assembly. Guardrail locks open and two hooking chains provide protected entry and exit. For added safety, the rail accommodates signs, flags, or lights. Conveniently it can be used with a guard rail tent, umbrellas, or our winch. Available in either 33" or 42" sizes.



Steel

- High quality steel
- Strong 1" diameter tubing
- 0.078-gauge steel
- Durable powder coated finish
- Safety yellow for high visibility

Features

- Designed to protect an area of 33" L x 33" W
- Support arm gives guardrail added support
- Two chains with hook for additional security
- Two welded market flags
- Simple one-piece construction assembles without the use of tools
- Collapses for compact storage

Part No.	Dimensions	Weight
9401	33" L x 33" W x 42-1/4" H	39 lb
9401-05	42" L x 42" W x 42-1/4" H	47 lb

*This assembly is to be used as a "Temporary Barrier Railing Only. See OSHA 1910.145(c)(5)(ii)(B)

Accessories

Part No.	Description	Part No.	Description	Part No.	Description
9403	Deluxe Umbrella	9401-10	Guard Rail Winch	9401-20	Manhole Lid Lifter
9403-03	Dielectric Umbrella	9401-12	Polymer Manhole Shield	9400-24	Manhole Sign 24"
9403-01	Economy Umbrella	9401-01	Guard Rail Tent	9400-26	Manhole Sign 26"

GUARDRAIL WINCH

Raising and lowering equipment into confined space can be impossible without this durable winch*. Even with a 300 lb. capacity, it is lightweight and portable, allowing easy mounting on guard rails**. The side pieces are constructed of high tensile, heavy-gauge aluminum with a durable yellow finish that resists weather and wear. The winch bar is constructed of rugged high tensile steel tubing with a 3" drum for fast recovery. Two independent ratchet systems, and a double-disc automatic brake offer load control and security. The 1/2" x 35" Nylon braided rope is strong and durable. Guard rail not included.



Used on our P/N 9401 Manhole Guardrail (See Above)

General Features

- 300 lb workload limit
- 3:1 safety factor
- 3" drum center
- 1" diameter center pipe 36" in length
- Two 7" discs (11" apart) to hold rope in place
- 1/2" holes (2" apart) accommodates 3/8" x 2-1/4" Loxall pins
- 9/16" Safety Snap Hook
- 35' x 1/2" Dura-Plex braided rope
- High quality steel length extensions painted yellow

Crank

- Gear covers
- Bronze
- Two independent ratchet systems for additional load security
- Double disc automatic load lock braking system to assure positive load control

Part No.	Dimensions	Weight
9401-10	43" L x 9-1/4" W x 32" H	39 lb

*This guardrail winch is intended for raising and lowering equipment into confined spaces. Not for use as a personal retrieval device.



QUADRA-FLEX ROLL UP SIGNS

Quadra Flex Roll-Up Signs are a quick and effective way to call attention to your work zone and are available in a variety of materials to meet your work zone needs.



Features

- NCHRP-350 Certified
- Meets MUTCD Specifications
- Lexan Polycarbonate pockets
- Ribs prevent splinters and fraying
- Available in 36" or 48"
- Fiberglass rib-set

Available Legends

- Arrow Left Symbol
- Arrow Right Symbol
- Arrow Up Symbol
- Be Prepared to Stop
- Bike Lane Closed
- Border Only
- Bump
- Construction Overhead Detour
- Do Not Pass Symbol (White)
- End Construction
- End Road Work
- Flagger Symbol
- Lane Closed
- Merge Left
- Merge Right
- Mower Ahead
- No Exit
- No Left Turn Symbol (White)
- No Right Turn Symbol (White)
- Ramp Closed
- Right Lane Closed
- Road Closed Ahead
- Rumble Strip Ahead
- Shoulder Closed
- Utility Construction Ahead
- Caution Construction
- One Land Road
- Yield Symbol (White)
- Worker Symbol
- No Shoulder
- Lane Closed Ahead

Available Material



Material	Orange	Pink	White	Lime	Yellow
Mesh Non-reflective	✓				
Vinyl Non-reflective	✓				
Super-bright Reflective	✓		✓		✓
Super-bright Fluorescent	✓	✓			
Marathon Fluorescent	✓		✓	✓	
Diamond Grade Reflective	✓		✓		



SIGN STANDS



TRI-POD



T-STAND



QUADRA-FLEX VI
Dual Spring Sign Stand



QUADRA-FLEX
Screw Lock Sign Stand

Part No.	Description
07822	Roll Up & Rigid Signs, 82" H

- Aluminum tripod
- Expands to accommodate a variety of signs
- Designed for good weather conditions for greater use
- For use with roll-up or rigid signs for greater versatility

Part No.	Description
07823	36" - 48" Roll Up Sign

- Aluminum Tripod Stand For Roll up Signs
- Orange
- For Emergency Response
- Stake at base allows to Firmly Drive Stand Into Ground
- Roll Up Sign Mounts Firmly to Top Frame Clips

Part No.	Description
78051	Aluminum Dual Spring Sign, 5" H

- Designed to meet your work zone signage needs
- Constructed of steel bases and aluminum mast and legs
- Allows deployment of roll-up signs at various heights between 14 in and 6 ft. from ground surface

Part No.	Description
07813-2	Dual Spring, 36" - 48" Roll Up Sign; 7' H

- Aircraft Aluminum alloy legs and uprights, with anti-skid rubber leg caps
- Steel base and spring components coated to withstand 500hrs of salt spray
- Adjustable legs for stability
- One-person deployment without tools

SAFETY CONES

DW SERIES

DW Series Cones are made with injection molded PVC, have a black rugged base and can withstand any weather conditions.

- NCHRP-350 Certified
- Meets MUTCD Standards
- Black rugged base
- Available with 4", 6" reflective collars or both
- Custom imprinting available



W SERIES

W Series Cones are designed with a solid orange base and made using injection molded PVC that can withstand any weather conditions.

- NCHRP-350 Certified
- Meets MUTCD Standards
- Injection Molded PVC - Solid
- Available with 4", 6" reflective collars or both
- Custom imprinting available



PACK N POP COLLAPSIBLE CONES

Pack N Pop Cones are standard sized cones in a compact format made with waterproof nylon that can withstand any weather conditions.

- Meets MUTCD Standards
- Constructed with orange waterproof nylon
- Collapses down to 2" high





W|ECO FOLDING FRAME ARROW BOARDS

W|ECO Folding Frame Arrow Boards are highly reliable, visible from distances of a mile or more, and employ a unique high-efficiency power system. The folding-frame design pivots the display panel up to the vertical position when deployed, and down to horizontal for transport. The display panel is secured in place with a single support that ensures ease of use and prevents damage. Both 15-light and 25-light models are available. Connected arrow boards can be accessed remotely using Wanco Fleet Manager.

Features

- Superior visibility
- Easy to operate and maintain
- 15-light and 25-light models
- Maintenance-free batteries
- Meets MUTCD

Operation

- High-output amber LEDs
- Selection of arrow and other display patterns
- Easy to operate and maintain
- Heavy-duty hand-winch with safety brake allows one person to raise board
- Single locking device holds arrow board in place while operating and during transport
- Controller located safely away from traffic
- Weather-resistant control box cover has lockable slam-latch
- Control box outputs have short-circuit protection, helping prevent blown transistors
- Arrow display has automatic dimming
- Stabilizer legs raise tires off the ground to provide stability in high wind

Specifications

Trailer: All welded Structural steel

Arrow Board: Aluminum sheet and welded channels

Coating: Powder-coated and oven-baked

Axle Assembly: 2,000 lb capacity tubular axle

5-hole 4.5" bolt circle pattern on idler hub

60" wheel track

Double eye leave springs, 1,200 lb capacity per spring

Tires: ST205/75/D15



Flashing Patterns

Pulse 1



Pulse 2



*Left or right †25-light models only

Sequential Patterns

Pulse 1




Pulse 2



Pulse 3



Pulse 4



*Left or right †25-light models only



W|ECO VERTICAL MAST ARROW BOARDS

W|ECO Vertical-Mast Arrow Boards feature a display panel that remains vertical at all times and rotates to face traffic. They are highly reliable, visible from distances of a mile or more, and employ a unique high-efficiency power system. The display is raised and lowered on a vertical tower using a hand-operated winch. Both 15-light and 25-light models are available. Connected arrow boards can be accessed remotely using Wanco Fleet Manager.

Features

- Display panel rotates freely to face traffic, 360 degrees
- Provides a clear view of road workers
- 15-light and 25-light models
- Maintenance-free batteries
- Meets MUTCD]

Operation

- High-output amber LEDs
- Selection of arrow and other display patterns
- Easy to operate and maintain
- Heavy-duty hand-winch with safety brake allows one person to raise display panel
- Display panel rotates freely for positioning without moving trailer
- Controller, batteries and all wiring mounted to display panel frame
- Weather-resistant control box cover has lockable slam-latch
- Control box outputs have short-circuit protection, helping prevent blown transistors
- Arrow display has automatic dimming
- Stabilizer legs raise tires off the ground to provide stability in high wind

Specifications

Trailer: All welded Structural steel

Arrow Board: Aluminum sheet and welded channels

Coating: Powder-coated and oven-baked

Axle Assembly: 2,000 lb capacity tubular axle
5-hole 4.5" bolt circle pattern on idler hub
60" wheel track

Double eye leave springs, 1,200 lb capacity per spring

Tires: ST205/75/D15



Flashing Patterns

Pulse 1



Pulse 2



*Left or right †25-light models only

Sequential Patterns

Pulse 1



Pulse 2



Pulse 3



Pulse 4



*Left or right †25-light models only



Stocking Locations

1300 National Ave Unit B
Addison, IL 60101

1440 Kings HWY
Haddon Heights, NJ 08035

888-206-3044

sales@builditright.us

www.builditright.us